



Ocean County Board of Commissioners

OFFICE OF THE
OCEAN COUNTY COMMISSIONERS

Director Frank Sadeghi
Deputy Director Jennifer Bacchione
Commissioner Robert S. Arace
Commissioner Sam Ellenbogen
Commissioner Ray Gormley

101 Hooper Avenue
Toms River, New Jersey
08754-2191
(732)929-2005
(732)505-1918

Board Meeting Agenda

Date: May 27, 2026 - 4:00 PM
Location: Administration Building
Room 119
101 Hooper Avenue
Toms River, NJ 08754

Agenda: Awarding a Contract for the furnishing and delivery of SOLAR POWERED LED AND SPEED RADAR SIGNS to National Highway Products, Inc., the lowest qualified bidder. (B2026-55)

Official Resolution#	2026000658
Meeting Date	05/27/2026
Introduced Date	05/27/2026
Adopted Date	05/27/2026
Agenda Item	I-3
CAF #	
Purchase Req. #	B2026-55
Result	Adopted

COUNTY COMMISSIONER	PRES.	ABS.	MOVE	SEC	AYE	NAY	ABST.
Sadeghi	✓				✓		
Bacchione	✓				✓		
Arace	✓			✓	✓		
Ellenbogen	✓				✓		
Gormley	✓		✓		✓		

I HEREBY CERTIFY THAT THIS DOCUMENT IS A TRUE, COMPLETE AND ACCURATE COPY OF THIS RESOLUTION, ADOPTED BY OCEAN COUNTY BOARD OF COMMISSIONERS, NJ AT THE MEETING REFERENCED THEREON

Michelle I. Gunther

Clerk Of The Board

RESOLUTION

May 27, 2026

WHEREAS, on March 31, 2026, pursuant to legal advertisements therefor, sealed bids were received for the furnishing and delivery of SOLAR POWERED LED AND SPEED RADAR SIGNS for the County of Ocean; and

WHEREAS, at the advertised time, responses were received from the following bidders:

<u>Name and Address of Bidder</u>	<u>Name and Address of Bidder</u>
National Highway Products, Inc. 301 Riverside Drive Millville, NJ 08332 (856) 692-7572	Eberl Iron Works, Inc. 128 Sycamore Street Buffalo, NY 14204 (716) 854-7633
Jonah's Enterprises, Inc. 652 Lefferts Avenue Brooklyn, NY 11203 (718) 502-8837	Lincoln Alloy 1720 Magnolia Drive Yuba City, CA 95991 (530) 709-8061
Sentinel Prime Group LLC 4725 W. Sand Lake Road Suite 203 Orlando, FL 32819 (407) 755-7102	Traffic Systems, Inc. 1 Corporate Drive Suite 1 Holtsville, NY 11742 (973) 823-0400

; and

WHEREAS, after receipt and examination of same, the County Purchasing Agent has now recommended to this Board that the lowest qualified bid, according to specifications, namely that of NATIONAL HIGHWAY PRODUCTS, INC., be accepted.

NOW, THEREFORE, BE IT RESOLVED by the BOARD OF COMMISSIONERS of the COUNTY OF OCEAN, STATE OF NEW JERSEY, as follows:

1. The Director and Clerk of this Board are hereby authorized and directed to enter into a contract, accepting the bid for the furnishing and delivery of Solar Powered LED and Speed Radar Signs for the County of Ocean, the contract shall be for one (1) year from date of award, or until delivery is complete unless otherwise stated. The County reserves the right to extend the term of the contract pursuant to N.J.S.A. 40A:11-15.

A. NATIONAL HIGHWAY PRODUCTS, INC. for thirty (30) items, to wit:
ITEM NOS. 1, 1A, 1B, 1C, 2, 2A, 2B, 2C, 3, 3A, 3B, 3C, 4, 4A, 4B, 4C, 5, 5A, 5B, 5C, 6, 6A, 6B, 6C, 7, 8, 9, 10, 11 and 12.
For a Total Lump Sum Award for Item Nos. 1 - 1C of \$ 19,180.00.
For a Total Lump Sum Award for Item Nos. 2 - 2C of \$ 60,690.00.
For a Total Lump Sum Award for Item Nos. 3 - 3C of \$113,150.00.

For a Total Lump Sum Award for Item Nos. 4 - 4C of \$ 12,590.00.

For a Total Lump Sum Award for Item Nos. 5 - 5C of \$ 8,990.00.

For a Total Lump Sum Award for Item Nos. 6 - 6C of \$ 11,965.00.

This vendor has extended this contract to County Cooperative Contract System Participants, Identifier No. CK-02-OC. All orders placed through the cooperative must reference the County Cooperative Identifier No. CK-02-OC.

2. Pursuant to N.J.A.C. 5:30-5.4, the County has established a reasonable estimated maximum dollar value of \$496,785.00 for the term of this contract, based on historical procurement data for comparable goods or services. The County further reserves the right to increase quantities by up to twenty percent (20%) of the maximum awarded amount at the unit prices bid, in accordance with N.J.A.C. 5:30-11.3.

3. Funds for the materials or services described herein shall be made available through operating and expense (O&E) accounts, trust accounts, grant accounts, or capital accounts maintained by, but not limited to, the following departments: Engineering Department.

4. Payments for the materials and services to be acquired by these contracts shall be made upon the approval of vouchers submitted by the successful bidders in accordance with the requirements of the Board of Commissioners and subject to the Board of Commissioners customary procedures. Delivery shall be made upon receipt of a Purchase Order issued by the Ocean County Department of Purchase, upon which delivery locations and needed quantities shall be indicated.

5. The contract number must be placed on all papers, documents, invoices and vouchers pertaining to said contract, the number being B2026-55.

Be it further resolved that certified copies of this Resolution shall be made available to the County Auditor, Purchasing Department, Finance Department, Engineering Department and National Highway Products, Inc., the successful bidder.

[NATIONAL HIGHWAY PRODUCTS, INC] RESPONSE DOCUMENT REPORT

Bid No. TBD

SOLAR POWERED LED AND SPEED RADAR SIGNS

ITEM #1 - 30" SOLAR POWERED LED SIGN ASSEMBLY

Line Item	Description	Quantity	Unit of Measure	Unit Cost	Total Cost	No Bid	Delivery A.R.O.	Comments
✓ 1	30" Solar Powered LED Sign Assembly, As Specified, or Equal	10	EA	\$1,420.00	\$14,200.00			TRAFFICALM
OPTIONS:								
✓ 1A	Steel Sign Post, As Specified	10	EA	\$35.00	\$350.00			
✓ 1B	Battery for Solar-Powered LED Sign Assembly, As Specified	10	EA	\$68.00	\$680.00			TRAFFICALM
✓ 1C	Solar Panel for Solar-Powered LED Sign Assembly, As Specified	10	EA	\$395.00	\$3,950.00			TRAFFICALM
TOTAL					\$19,180.00			

ITEM #2 - 36" SOLAR POWERED LED SIGN ASSEMBLY

Line Item	Description	Quantity	Unit of Measure	Unit Cost	Total Cost	No Bid	Delivery A.R.O.	Comments
✓ 2	36" Solar Powered LED Sign Assembly, As Specified, or Equal	30	EA	\$1,525.00	\$45,750.00			TRAFFICALM
OPTIONS:								
✓ 2A	Steel Sign Post, As Specified	30	EA	\$35.00	\$1,050.00			
✓ 2B	Battery for Solar-Powered LED Sign Assembly, As Specified	30	EA	\$68.00	\$2,040.00			TRAFFICALM
✓ 2C	Solar Panel for Solar-Powered LED Sign Assembly, As Specified	30	EA	\$395.00	\$11,850.00			TRAFFICALM
TOTAL					\$60,690.00			

ITEM #3 - 48" SOLAR POWERED LED SIGN ASSEMBLY

Introduced on: May 27, 2026

Adopted on: May 27, 2026

Official Resolution#: 2026000658

Bid - SOLAR POWERED LED AND SPEED RADAR SIGNS

[NATIONAL HIGHWAY PRODUCTS, INC] RESPONSE DOCUMENT REPORT

Bid No. TBD

SOLAR POWERED LED AND SPEED RADAR SIGNS

Line Item	Description	Quantity	Unit of Measure	Unit Cost	Total Cost	No Bid	Delivery A.R.O.	Comments
✓ 3	48" Solar Powered LED Sign Assembly, As Specified, or Equal	50	EA	\$1,695.00	\$84,750.00			TRAFFICALM
OPTIONS:								
✓ 3A	Steel Sign Post, As Specified	50	EA	\$35.00	\$1,750.00			
✓ 3B	Battery for Solar-Powered LED Sign Assembly, As Specified	50	EA	\$138.00	\$6,900.00			TRAFFICALM
✓ 3C	Solar Panel for Solar-Powered LED Sign Assembly, As Specified	50	EA	\$395.00	\$19,750.00			TRAFFICALM
TOTAL					\$113,150.00			

ITEM #4 - 48" X 24" SOLAR POWERED LED SIGN ASSEMBLY

Line Item	Description	Quantity	Unit of Measure	Unit Cost	Total Cost	No Bid	Comments
✓ 4	48" X 24" Solar Powered LED Sign Assembly, As Specified, or Equal	5	EA	\$1,950.00	\$9,750.00		TRAFFICALM
OPTIONS:							
✓ 4A	Steel Sign Post, As Specified	5	EA	\$35.00	\$175.00		
✓ 4B	Battery for Solar-Powered LED Sign Assembly, As Specified	5	EA	\$138.00	\$690.00		TRAFFICALM
✓ 4C	Solar Panel for Solar-Powered LED Sign Assembly, As Specified	5	EA	\$395.00	\$1,975.00		TRAFFICALM
TOTAL					\$12,590.00		

ITEM #5 - 24" X 30" SOLAR POWERED LED SIGN ASSEMBLY

Line Item	Description	Quantity	Unit of Measure	Unit Cost	Total Cost	No Bid	Comments
✓ 5	24" X 30" Solar Powered LED Sign Assembly, As Specified, or Equal	5	EA	\$1,300.00	\$6,500.00		TRAFFICALM

Introduced on: May 27, 2026

Adopted by: NATIONAL HIGHWAY PRODUCTS, INC] RESPONSE DOCUMENT REPORT

Official Resolution#: 2026000658

BID SOLAR POWERED LED AND SPEED RADAR SIGNS

[NATIONAL HIGHWAY PRODUCTS, INC] RESPONSE DOCUMENT REPORT

Bid No. TBD

SOLAR POWERED LED AND SPEED RADAR SIGNS

Line Item	Description	Quantity	Unit of Measure	Unit Cost	Total Cost	No Bid	Comments
OPTIONS:							
✓ 5A	Steel Sign Post, As Specified	5	EA	\$35.00	\$175.00		
✓ 5B	Battery for Solar-Powered LED Sign Assembly, As Specified	5	EA	\$68.00	\$340.00		TRAFFICALM
✓ 5C	Solar Panel for Solar-Powered LED Sign Assembly, As Specified	5	EA	\$395.00	\$1,975.00		TRAFFICALM
TOTAL					\$8,990.00		

ITEM #6 - 30" X 36" SOLAR POWERED LED SIGN ASSEMBLY

Line Item	Description	Quantity	Unit of Measure	Unit Cost	Total Cost	No Bid	Comments
✓ 6	30" X 36" Solar Powered LED Sign Assembly, As Specified, or Equal	5	EA	\$1,825.00	\$9,125.00		TRAFFICALM
OPTIONS:							
✓ 6A	Steel Sign Post, As Specified	5	EA	\$35.00	\$175.00		
✓ 6B	Battery for Solar-Powered LED Sign Assembly, As Specified	5	EA	\$138.00	\$690.00		TRAFFICALM
✓ 6C	Solar Panel for Solar-Powered LED Sign Assembly, As Specified	5	EA	\$395.00	\$1,975.00		TRAFFICALM
TOTAL					\$11,965.00		

SOLAR SPEED RADAR SIGNS AND ACCESSORIES, ITEM #'S 7 - 12

Line Item	Description	Quantity	Unit of Measure	Unit Cost	Total Cost	No Bid	Comments
✓ 7	Solar Speed Radar Sign, 12", Traffic Logix Safespace Evolution 12, As Specified, or Equal	4	EA	\$4,200.00	\$16,800.00		TRAFFICALM
✓ 8	Solar Speed Radar Sign, 15", Traffic Logix Safespace 450 Full Radar Speed Sign, As Specified, or Equal	50	EA	\$4,400.00	\$220,000.00		TRAFFICALM

Introduced on: May 27, 2026

Adopted by: NATIONAL HIGHWAY PRODUCTS, INC] RESPONSE DOCUMENT REPORT

Official Resolution#: 2026009658

BID - SOLAR POWERED LED AND SPEED RADAR SIGNS

[NATIONAL HIGHWAY PRODUCTS, INC] RESPONSE DOCUMENT REPORT

Bid No. TBD

SOLAR POWERED LED AND SPEED RADAR SIGNS

Line Item	Description	Quantity	Unit of Measure	Unit Cost	Total Cost	No Bid	Comments
✓ 9	Steel Sign Post, As Specified, or Equal	30	EA	\$35.00	\$1,050.00		
✓ 10	Battery for Solar-Powered LED Sign Assembly, As Specified, or Equal	30	EA	\$68.00	\$2,040.00		FOR USE WITH TRAFFICALM SYSTEMS ONLY
✓ 11	Solar Panel for Solar-Powered LED Sign Assembly, As Specified, or Equal	30	EA	\$395.00	\$11,850.00		FOR USE WITH TRAFFICALM SYSTEMS
✓ 12	Solar-Powered LED Pedestrian Crossing Warning System with Push Buttons, As Specified, or Equal	4	EA	\$4,620.00	\$18,480.00		TRAFFICALM

Introduced on: May 27, 2026

Adopted on: May 27, 2026

Official Resolution # 2026000058

ITEM #1 - 30" SOLAR POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL**COMPLIANCE****YES** **NO****DESCRIPTION:**

Solar Powered and fully self-contained sign assembly conforming to the U.S. Department of Transportation Federal Highway Administration 2009 revision 2 May 2012 Manual on Uniform Traffic Control Devices section 2A.08 on retro reflectivity and illumination.

☒ ☐**MATERIALS:**

The assembly shall include the following items:

☒ ☐**SIGN:**

Sign blanks shall be .080" gauge aluminum

☒ ☐

Sheeting shall be 3M DG Type IX or approved equal, with anti-graffiti overlay

☒ ☐

Sign assembly shall use anti-vandal fastener to mount components to sign and sign for fixture

☒ ☐

Mounting hardware shall be Stainless Steel 5/16"

☒ ☐**LED:**

Sign assembly shall utilize high-power 1W LEDs that provide a maximum light intensity of up to 600,000 mcd (millicandelas) with a viewing angle of 20 degrees.

☐ ☒

The various sign faces shall have a color and minimum number of LEDs as noted below:

	<u>SIGN</u>	<u>LED Color</u>	<u>Minimum Number</u>		
Ped Crossing 30" x 30" (Facing) Fluorescent Yellow Green	W11-2	White or Yellow	8	☒	☐
Turn Symbol 30" x 30" (Facing) Yellow	W1-1L	White or Yellow	8	☒	☐
Turn Symbol 30" x 30" (Facing) Yellow	W1-1R	White or Yellow	8	☒	☐
Curve Symbol 30" x 30" (Facing) Yellow	W1-2L	White or Yellow	8	☒	☐
Curve Symbol 30" x 30" (Facing) Yellow	W1-2R	White or Yellow	8	☒	☐
Stop Ahead 30" x 30" Stop Symbol, White on Red, Border & Arrow Black On Yellow (Facing)	W3-1	White or Yellow	8	☒	☐
Yield Ahead 30" x 30" Stop Symbol, White on Red, Border & Arrow Black On Yellow (Facing)	W3-2	White or Yellow	8	☒	☐

ITEM #1 – 30" SOLAR-POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL (CONT'D)

				<u>COMPLIANCE</u>	
				<u>YES</u>	<u>NO</u>
	<u>SIGN</u>	<u>LED Color</u>	<u>Minimum Number</u>		
Signal Ahead 30" x 30" Symbol, Border & Arrow Black on (Facing) Yellow	W3-3	White or Yellow	8	☒	☐
<u>LED: (CONT'D)</u>					
Each LED shall be sealed in a heat-dissipating plastic enclosure to provide resistance to weather and vibration.				☒	☐
Each LED enclosure shall be mounted to the sign in a 1" hole and ultrasonically welded or mechanically fastened to the sign assembly.				☐	☒
All LEDs shall be wired in strings to activate simultaneously (as per MUTCD standard).				☒	☐
All wire used shall conform to military specification MIL-W-16878D, Type D, vinyl nylon jacket.				☒	☐
Wiring shall be covered and secured to the sign assembly in a weather resistant enclosure.				☒	☐
All LED connectors shall conform to Ingress Protection IP-65 rating or better.				☒	☐
<u>SOLAR PANEL:</u>					
Solar panels shall be sized appropriately so as to maintain the battery sufficiently to ensure operation in the Ocean County Region.				☒	☐
All panels shall be mounted to an aluminum plate and bracket at an angle of 45° to 60°.				☒	☐
All fasteners used shall be anti-vandal.				☒	☐
Wire used shall conform to military specification MIL-W-16878D, Type D, vinyl nylon jacket.				☒	☐
The solar panel assembly shall be mounted securely to the sign assembly.				☐	☒
All solar panel connectors shall conform to Ingress Protection IP-65 rating or better.				☒	☐
<u>CONTROL CIRCUIT:</u>					
Control circuit shall have the capability of independently flashing dual outputs.				☒	☐
Flashing output shall be 50 to 60 flashes per minute with 100 ms duration on time. Outputs shall reach the output current as programmed for the duration of the 100 ms pulse.				☒	☐
Output current shall be individually programmable for daytime and nighttime operation for the purpose of adjusting to ambient lighting conditions. Mode will automatically be determined by solar panel charge input.				☒	☐
Control circuit covering shall be waterproof and anti-vandal.				☒	☐
Control circuit shall remain operational between the temperatures of -40°F and 176°F.				☒	☐
All circuit connectors shall conform to Ingress Protection IP-65 rating or better.				☐	☐

**ITEM #1 – 30" SOLAR-POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL
(CONT'D)****COMPLIANCE****YES** **NO****BATTERY:**

Battery packs shall be 4.8V, 14 Ah nickel metal hydride (NiMH).

☐ ☒

Batteries shall be sealed in a plastic film to provide resistance to moisture and corrosion.

☐ ☒

Batteries shall remain operational between the temperatures of -40°F and 176°F, and shall utilize overheat protection.

☒ ☐

All battery connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐

Batteries shall not weigh more than 1.8 lbs.

☒ ☐

Batteries shall have a waterproof connection

☒ ☐

Batteries shall be sealed and spill-proof

☒ ☐

Batteries shall have an in-line power connector

☒ ☐

Batteries shall be replaceable independently of other components

☒ ☐

Batteries shall be fused for short circuit protection

☒ ☐

Batteries shall be protected from overheating by means of a thermocouple sensor

☒ ☐

Batteries shall have the following dimensions:

Grouped: 2.66" H X 2.66" W X 2.78" D

☐ ☒

Stacked: 1.34" H X 1.34" W X 10.6" D

☐ ☒

Flatpack: 5.24" H X 2.68" W X 0.67" D

☐ ☒**WARRANTY:**

Manufacturer shall offer (at minimum) one (1) year of unconditional warranty against all defects in material and workmanship.

☒ ☐

**ITEM #1 – 30" SOLAR-POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL
(CONT'D)****COMPLIANCE**
YES **NO****OPTIONS:****1A – Steel Sign Post, As Specified****Description:**Nucor RIB-BAK U-Channel Sign Support, galvanized, without breakaway
(or approved equal).☒ ☐**Measurements:**

10' length

☒ ☐

3-1/16" width

☒ ☐

3/8" holes on 1" centers

☒ ☐

2.5 lbs/ft linear weight

☒ ☐**Materials:**

Mounting hardware shall be Stainless Steel 5/16"

☒ ☐**1B - Battery For Solar-Powered LED Sign Assembly, As Specified****Description:**6V, 14 Ah nickel metal hydride (NiMH) battery pack compatible with TAPCO®
Blinkersigns®.☐ ☒**Materials:**Batteries shall be sealed in a plastic film to provide resistance to moisture and
corrosion.☐ ☒**Battery:**

Batteries shall not weigh more than 1.8 lbs.

☒ ☐

Batteries shall have a waterproof connection

☒ ☐

Batteries shall be sealed and spill-proof

☒ ☐

Batteries shall have an in-line power connector

☒ ☐

Batteries shall be replaceable independently of other components

☒ ☐

Batteries shall be fused for short circuit protection

☒ ☐

Batteries shall be protected from overheating by means of a thermocouple sensor

☒ ☐

Batteries shall have the following dimensions:

Grouped: 2.66" H X 2.66" W X 2.78" D

☐ ☒

Stacked: 1.34" H X 1.34" W X 10.6" D

☐ ☒Flatpack: 5.74" H X 2.68" W X 0.67" D
Introduced on: May 27, 2026
Adopted on: May 27, 2026
Official Resolution#: 2026000658☐ ☒

ITEM #1 – 30" SOLAR-POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL (CONT'D)

COMPLIANCE
YES **NO**

OPTIONS: (CONT'D)

1B - Battery For Solar-Powered Led Sign Assembly, As Specified (Cont'd)

Operation:

Batteries shall remain operational between the temperatures of -40°F and 176°F (-40°C and 80°C), and shall utilize overheat protection.

☒ ☐

Electrical:

All battery connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐

1C - Solar Panel For Solar-Powered LED Sign Assembly, As Specified

Description:

Solar panel compatible with TAPCO® Blinkersigns® and of the correct size and parameters as necessary to maintain operation of a solar-powered LED sign assembly in the Ocean County Region.

☐ ☒

Mounting:

The solar panel assembly shall be mounted securely to the sign assembly.

☐ ☒

All panels shall be mounted to an aluminum plate and bracket at an angle of 45° to 60°.

☒ ☐

Hardware:

All fasteners used shall be anti-vandal.

☒ ☐

Electrical:

Wire used shall conform to military specification MIL-W-16878D, Type D, vinyl nylon jacket.

☒ ☒

All solar panel connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐

ITEM #2 - 36" SOLAR POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL**COMPLIANCE****YES** **NO****DESCRIPTION:**

Solar Powered and fully self-contained sign assembly conforming to the U.S. Department of Transportation Federal Highway Administration 2009 revision 2 May 2012 Manual on Uniform Traffic Control Devices section 2A.08 on retro reflectivity and illumination.

☒ ☐
MATERIALS:

The assembly shall include the following items:

SIGN:

Sign blanks shall be .080" gauge aluminum

☒ ☐

Sheeting shall be 3M DG Type IX or approved equal, with anti-graffiti overlay

☒ ☐

Sign assembly shall use anti-vandal fastener to mount components to sign and sign for fixture

☒ ☐

36" Signs shall have four (4) holes punched to allow dual post mounting

☒ ☐

Mounting hardware shall be Stainless Steel 5/16"

☒ ☐
LED:

Sign assembly shall utilize high-power 1W LEDs that provide a maximum light intensity of up to 600,000 mcd (millicandelas) with a viewing angle of 20 degrees.

☐ ☒

The various sign faces shall have a color and minimum number of LEDs as noted below:

	<u>SIGN</u>	<u>LED Color</u>	<u>Minimum Number</u>		
Stop 36" x 36" (Facing)(White on Red)	R1-1	White or Red	8	☒	☐
Yield 36" x 36" x 36" (Facing)(White on Red)	R1-2	White or Red	9	☒	☐
School Crossing (Symbol) 36" x 36" (Facing) Fluorescent Yellow Green/ Black/ Red	S1-1	White or Yellow	6	☒	☐
Ped Crossing 36" x 36" (Facing) Fluorescent Yellow Green	W11-2	White or Yellow	8	☒	☐
Turn Symbol 36" x 36" (Facing) Yellow	W1-1L	White or Yellow	8	☒	☐
Turn Symbol 36" x 36" (Facing) Yellow	W1-1R	White or Yellow	8	☒	☐
Turn Symbol L / speed 36" x 36" (MPH) to be noted at time of order (Facing) Yellow	W1-1a	White or Yellow	8	☒	☐

**ITEM #2 - 36" SOLAR POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL
(CONT'D)**

				<u>COMPLIANCE</u>	
				<u>YES</u>	<u>NO</u>
<u>LED: (CONT'D)</u>					
	<u>SIGN</u>	<u>LED Color</u>	<u>Minimum Number</u>		
Turn Symbol R / speed 36" x 36" (MPH) to be noted at time of order (Facing) Yellow	W1-1a	White or Yellow	8	☒	☐
Curve Symbol 36" x 36" (Facing) Yellow	W1-2L	White or Yellow	8	☒	☐
Curve Symbol 36" x 36" (Facing) Yellow	W1-2R	White or Yellow	8	☒	☐
Curve Symbol L / speed 36" x 36"(MPH) to be noted at time of order (Facing) Yellow	W1-2a	White or Yellow	8	☒	☐
Curve Symbol R / speed 36" x 36" (MPH) to be noted at time of order (Facing) Yellow	W1-2a	White or Yellow	8	☒	☐
Each LED shall be sealed in a heat-dissipating plastic enclosure to provide resistance to weather and vibration.				☒	☐
Each LED enclosure shall be mounted to the sign in a 1" hole and ultrasonically welded or mechanically fastened to the sign assembly.				☒	☐
All LEDs shall be wired in strings to activate simultaneously (as per MUTCD standard).				☒	☐
All wire used shall conform to military specification MIL-W-16878D, Type D, vinyl nylon jacket.				☒	☐
Wiring shall be covered and secured to the sign assembly in a weather resistant enclosure.				☒	☐
All LED connectors shall conform to Ingress Protection IP-65 rating or better.				☒	☐
<u>SOLAR PANEL:</u>					
Solar panels shall be sized appropriately so as to maintain the battery sufficiently to ensure operation in the Ocean County Region.				☒	☐
All panels shall be mounted to an aluminum plate and bracket at an angle of 45° to 60°.				☒	☐
All fasteners used shall be anti-vandal.				☒	☐
Wire used shall conform to military specification MIL-W-16878D, Type D, vinyl nylon jacket.				☒	☐
The solar panel assembly shall be mounted securely to the sign assembly.				☒	☐
All solar panel connectors shall conform to Ingress Protection IP-65 rating or better.				☒	☐

**ITEM #2 - 36" SOLAR POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL
(CONT'D)****COMPLIANCE****YES****NO****CONTROL CIRCUIT:**

Control circuit shall have the capability of independently flashing dual outputs.

☒☐

Flashing output shall be 50 to 60 flashes per minute with 100 ms duration on time.

Outputs shall reach the output current as programmed for the duration of the 100 ms pulse.

☒☐

Output current shall be individually programmable for daytime and nighttime operation for the purpose of adjusting to ambient lighting conditions. Mode will automatically be determined by solar panel charge input.

☒☐

Control circuit covering shall be waterproof and anti-vandal.

☒☐

Control circuit shall remain operational between the temperatures of -40°F and 176°F.

☒☐

All circuit connectors shall conform to Ingress Protection IP-65 rating or better.

☒☐**BATTERY:**

Battery packs shall be 4.8V, 14 Ah nickel metal hydride (NiMH).

☐☒

Batteries shall be sealed in a plastic film to provide resistance to moisture and corrosion.

☐☒

Batteries shall remain operational between the temperatures of -40°F and 176°F, and shall utilize overheat protection.

☒☐

All battery connectors shall conform to Ingress Protection IP-65 rating or better.

☒☐

Batteries shall not weigh more than 1.8 lbs.

☐☒

Batteries shall have a waterproof connection

☒☐

Batteries shall be sealed and spill-proof

☒☐

Batteries shall have an in-line power connector

☒☐

Batteries shall be replaceable independently of other components

☒☐

Batteries shall be fused for short circuit protection

☒☐

Batteries shall be protected from overheating by means of a thermocouple sensor

☒☐

Batteries shall have the following dimensions:

Grouped: 2.66" H X 2.66" W X 2.78" D

☐☒

Stacked: 1.34" H X 1.34" W X 10.6" D

☐☒

Flatpack: 5.24" H X 2.68" W X 0.67" D

☐☒**WARRANTY:**

Manufacturer shall offer (at minimum) one (1) year of unconditional warranty against all defects in material and workmanship.

☒☐

**ITEM #2 - 36" SOLAR POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL
(CONT'D)****COMPLIANCE****YES** **NO****OPTIONS:****2A – Steel Sign Post, As Specified****Description:**

Nucor RIB-BAK U-Channel Sign Support, galvanized (or approved equal).

☒ ☐**Measurements:**

10' length

☒ ☐

3-1/16" width

☒ ☐

3/8" holes on 1" centers

☒ ☐

2.5 lbs/ft linear weight

☒ ☐**Materials:**

Mounting hardware shall be Stainless Steel 5/16"

☒ ☐**2B - Battery For Solar-Powered LED Sign Assembly, As Specified****Description:**

6V, 14 Ah nickel metal hydride (NiMH) battery pack compatible with TAPCO® Blinkersigns®.

☐ ☒**Materials:**

Batteries shall be sealed in a plastic film to provide resistance to moisture and corrosion.

☐ ☒**Battery:**

Batteries shall not weigh more than 1.8 lbs.

☐ ☒

Batteries shall have a waterproof connection

☒ ☐

Batteries shall be sealed and spill-proof

☒ ☐

Batteries shall have an in-line power connector

☒ ☐

Batteries shall be replaceable independently of other components

☒ ☐

Batteries shall be fused for short circuit protection

☒ ☐

Batteries shall be protected from overheating by means of a thermocouple sensor

☒ ☐

Batteries shall have the following dimensions:

Grouped: 2.66" H X 2.66" W X 2.78" D

☐ ☒

Stacked: 1.34" H X 1.34" W X 10.6" D

☐ ☒

Flatpack: 5.24" H X 2.68" W X 0.67" D

☐ ☒

**ITEM #2 - 36" SOLAR POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL
(CONT'D)****COMPLIANCE**
YES NO**OPTIONS: (CONT'D)****2B - Battery For Solar-Powered LED Sign Assembly, As Specified (Cont'd)****Operation:**

Batteries shall remain operational between the temperatures of -40°F and 176°F (-40°C and 80°C), and shall utilize overheat protection.

☒ ☐

Electrical:

All battery connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐

2C - Solar Panel For Solar-Powered LED Sign Assembly, As Specified**Description:**

Solar panel compatible with TAPCO® Blinkersigns® and of the correct size and parameters as necessary to maintain operation of a solar-powered LED sign assembly in the Ocean County Region.

☐ ☒

Mounting:

The solar panel assembly shall be mounted securely to the sign assembly.

☐ ☒

All panels shall be mounted to an aluminum plate and bracket at an angle of 45° to 60°.

☒ ☐

Hardware:

All fasteners used shall be anti-vandal.

☒ ☐

Electrical:

Wire used shall conform to military specification MIL-W-16878D, Type D, vinyl nylon jacket.

☒ ☐

All solar panel connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐

ITEM #3 - 48" SOLAR POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL

COMPLIANCE

YES **NO**

DESCRIPTION:

Solar Powered and fully self-contained sign assembly conforming to the U.S. Department of Transportation Federal Highway Administration 2009 revision 2 May 2012 Manual on Uniform Traffic Control Devices section 2A.08 on retro reflectivity and illumination.

☒ ☐

MATERIALS:

The assembly shall include the following items:

SIGN:

Sign blanks shall be .080" gauge aluminum

☒ ☐

Sheeting shall be 3M DG Type IX or approved equal, with anti-graffiti overlay

☒ ☐

Sign assembly shall use anti-vandal fastener to mount components to sign and sign for fixture

☒ ☐

48" Signs shall have four (4) holes punched to allow dual post mounting

☒ ☐

Mounting hardware shall be Stainless Steel 5/16"

☒ ☐

LED:

Sign assembly shall utilize high-power 1W LEDs that provide a maximum light intensity of up to 600,000 mcd (millicandelas) with a viewing angle of 20 degrees.

☐ ☒

The sign faces shall have a color and minimum number of LEDs as noted below:

	<u>SIGN</u>	<u>LED Color</u>	<u>Minimum Number</u>		
Stop 48" x 48" (Facing)(White on Red)	R1-1	White or Red	8	☒	☐
Each LED shall be sealed in a heat-dissipating plastic enclosure to provide resistance to weather and vibration.				☒	☐
Each LED enclosure shall be mounted to the sign in a 1" hole and ultrasonically welded or mechanically fastened to the sign assembly.				☒	☐
All LEDs shall be wired in strings to activate simultaneously (as per MUTCD standard).				☒	☐
All wire used shall conform to military specification MIL-W-16878D, Type D, vinyl nylon jacket.				☒	☐
Wiring shall be covered and secured to the sign assembly in a weather resistant enclosure.				☒	☐
All LED connectors shall conform to Ingress Protection IP-65 rating or better.				☒	☐

ITEM #3 - 48" SOLAR POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL (CONT'D)

	<u>COMPLIANCE</u>	
	<u>YES</u>	<u>NO</u>
<u>SOLAR PANEL:</u>		
Solar panels shall be sized appropriately so as to maintain the battery sufficiently to ensure operation in the Ocean County Region.	☒	☐
All panels shall be mounted to an aluminum plate and bracket at an angle of 45° to 60°.	☒	☐
All fasteners used shall be anti-vandal.	☒	☐
Wire used shall conform to military specification MIL-W-16878D, Type D, vinyl nylon jacket.	☒	☐
The solar panel assembly shall be mounted securely to the sign assembly.	☐	☒
All solar panel connectors shall conform to Ingress Protection IP-65 rating or better.	☒	☐
<u>CONTROL CIRCUIT:</u>		
Control circuit shall have the capability of independently flashing dual outputs.	☒	☐
Flashing output shall be 50 to 60 flashes per minute with 100 ms duration on time. Outputs shall reach the output current as programmed for the duration of the 100 ms pulse.	☒	☐
Output current shall be individually programmable for daytime and nighttime operation for the purpose of adjusting to ambient lighting conditions. Mode will automatically be determined by solar panel charge input.	☒	☐
Control circuit covering shall be waterproof and anti-vandal.	☒	☐
Control circuit shall remain operational between the temperatures of -40°F and 176°F.	☒	☐
All circuit connectors shall conform to Ingress Protection IP-65 rating or better.	☒	☐
<u>BATTERY:</u>		
Battery packs shall be 4.8V, 14 Ah nickel metal hydride (NiMH).	☐	☒
Batteries shall be sealed in a plastic film to provide resistance to moisture and corrosion.	☐	☒
Batteries shall remain operational between the temperatures of -40°F and 176°F, and shall utilize overheat protection.	☒	☐
All battery connectors shall conform to Ingress Protection IP-65 rating or better.	☒	☐
Batteries shall not weigh more than 1.8 lbs.	☒	☐
Batteries shall have a waterproof connection	☒	☐
Batteries shall be sealed and spill-proof	☒	☐
Batteries shall have an in-line power connector	☒	☐
Batteries shall be replaceable independently of other components	☒	☐
Batteries shall be fused for short circuit protection	☒	☐
Batteries shall be protected from overheating by means of a thermocouple sensor	☒	☐

**ITEM #3 - 48" SOLAR POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL
(CONT'D)**

COMPLIANCE
YES NO

BATTERY: (CONT'D)

Batteries shall have the following dimensions:

Grouped: 2.66" H X 2.66" W X 2.78" D

☐ ☒

Stacked: 1.34" H X 1.34" W X 10.6" D

☐ ☒

Flatpack: 5.24" H X 2.68" W X 0.67" D

☐ ☒

WARRANTY:

Manufacturer shall offer (at minimum) one (1) year of unconditional warranty against all defects in material and workmanship.

☒ ☐

OPTIONS:

3A – Steel Sign Post, As Specified

Description:

Nucor RIB-BAK U-Channel Sign Support, galvanized (or approved equal).

☒ ☐

Measurements:

10' length

☒ ☐

3-1/16" width

☒ ☐

3/8" holes on 1" centers

☒ ☐

2.5 lbs/ft linear weight

☒ ☐

Materials:

Mounting hardware shall be Stainless Steel 5/16"

☒ ☐

3B - Battery For Solar-Powered LED Sign Assembly, As Specified

Description:

6V, 14 Ah nickel metal hydride (NiMH) battery pack compatible with TAPCO® Blinkersigns®.

☐ ☒

Materials:

Batteries shall be sealed in a plastic film to provide resistance to moisture and corrosion.

☐ ☒

Battery:

Batteries shall not weigh more than 1.8 lbs.

☒ ☐

Batteries shall have a waterproof connection

☒ ☐

Batteries shall be sealed and spill-proof

☒ ☐

Batteries shall have an in-line power connector

☒ ☐

Batteries shall be replaceable independently of other components

☒ ☐

ITEM #3 - 48" SOLAR POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL (CONT'D)**COMPLIANCE**
YES **NO****OPTIONS: (CONT'D)****3B - Battery For Solar-Powered LED Sign Assembly, As Specified (Cont'd)****Battery: (Cont'd)**

Batteries shall be fused for short circuit protection

☒ ☐

Batteries shall be protected from overheating by means of a thermocouple sensor

☒ ☐

Batteries shall have the following dimensions:

Grouped: 2.66" H X 2.66" W X 2.78" D

☐ ☒

Stacked: 1.34" H X 1.34" W X 10.6" D

☐ ☒

Flatpack: 5.24" H X 2.68" W X 0.67" D

☐ ☒**Operation:**

Batteries shall remain operational between the temperatures of -40°F and 176°F (-40°C and 80°C), and shall utilize overheat protection.

☒ ☐**Electrical:**

All battery connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐**3C - Solar Panel For Solar-Powered LED Sign Assembly, As Specified****Description:**

Solar panel compatible with TAPCO® Blinkersigns® and of the correct size and parameters as necessary to maintain operation of a solar-powered LED sign assembly in the Ocean County Region.

☐ ☒**Mounting:**

The solar panel assembly shall be mounted securely to the sign assembly.

☐ ☒

All panels shall be mounted to an aluminum plate and bracket at an angle of 45° to 60°.

☒ ☐**Hardware:**

All fasteners used shall be anti-vandal.

☒ ☐**Electrical:**

Wire used shall conform to military specification MIL-W-16878D, Type D, vinyl nylon jacket.

☒ ☐

All solar panel connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐

ITEM #4 - 48" x 24" SOLAR POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL**DESCRIPTION:**

Solar Powered and fully self-contained sign assembly conforming to the U.S. Department of Transportation Federal Highway Administration 2009 revision 2 May 2012 Manual on Uniform Traffic Control Devices section 2A.08 on retro reflectivity and illumination.

☒ ☐
MATERIALS:

The assembly shall include the following items:

SIGN:

Sign blanks shall be .080" gauge aluminum

☒ ☐

Sheeting shall be 3M DG Type IX or approved equal, with anti-graffiti overlay

☒ ☐

Sign assembly shall use anti-vandal fastener to mount components to sign and sign for fixture

☒ ☐

48" Signs shall have four (4) holes punched to allow dual post mounting

☒ ☐

Mounting hardware shall be Stainless Steel 5/16"

☒ ☐
LED:

Sign assembly shall utilize high-power 1W LEDs that provide a maximum light intensity of up to 600,000 mcd (millicandelas) with a viewing angle of 20 degrees.

☐ ☒

The sign faces shall have a color and minimum number of LEDs as noted below:

	<u>SIGN</u>	<u>LED Color</u>	<u>Minimum Number</u>		
Large Arrow Left 48" x 24" (Facing) Black on Yellow	W1-6L	White or Yellow	8	☒	☐
Large Arrow Right 48" x 24" (Facing) Black on Yellow	W1-6R	White or Yellow	8	☒	☐
Each LED shall be sealed in a heat-dissipating plastic enclosure to provide resistance to weather and vibration.				☒	☐
Each LED enclosure shall be mounted to the sign in a 1" hole and ultrasonically welded or mechanically fastened to the sign assembly.				☒	☐
All LEDs shall be wired in strings to activate simultaneously (as per MUTCD standard).				☒	☐
All wire used shall conform to military specification MIL-W-16878D, Type D, vinyl nylon jacket.				☒	☐
Wiring shall be covered and secured to the sign assembly in a weather resistant enclosure.				☒	☐
All LED connectors shall conform to Ingress Protection IP-65 rating or better.				☒	☐

ITEM #4 - 48" x 24" SOLAR POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL (CONT'D)**COMPLIANCE****YES** **YES****SOLAR PANEL:**

Solar panels shall be sized appropriately so as to maintain the battery sufficiently to ensure operation in the Ocean County Region.

☒ ☐

All panels shall be mounted to an aluminum plate and bracket at an angle of 45° to 60°.

☒ ☐

All fasteners used shall be anti-vandal.

☒ ☐

Wire used shall conform to military specification MIL-W-16878D, Type D, vinyl nylon jacket.

☒ ☐

The solar panel assembly shall be mounted securely to the sign assembly.

☐ ☒

All solar panel connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐**CONTROL CIRCUIT:**

Control circuit shall have the capability of independently flashing dual outputs.

☒ ☐

Flashing output shall be 50 to 60 flashes per minute with 100 ms duration on time. Outputs shall reach the output current as programmed for the duration of the 100 ms pulse.

☒ ☐

Output current shall be individually programmable for daytime and nighttime operation for the purpose of adjusting to ambient lighting conditions. Mode will automatically be determined by solar panel charge input.

☒ ☐

Control circuit covering shall be waterproof and anti-vandal.

☒ ☐

Control circuit shall remain operational between the temperatures of -40°F and 176°F.

☒ ☐

All circuit connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐**BATTERY:**

Battery packs shall be 4.8V, 14 Ah nickel metal hydride (NiMH).

☐ ☒

Batteries shall be sealed in a plastic film to provide resistance to moisture and corrosion.

☒ ☐

Batteries shall remain operational between the temperatures of -40°F and 176°F, and shall utilize overheat protection.

☒ ☐

All battery connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐

Batteries shall not weigh more than 1.8 lbs.

☒ ☐

Batteries shall have a waterproof connection

☒ ☐

Batteries shall be sealed and spill-proof

☒ ☐

Batteries shall have an in-line power connector

☒ ☐

Batteries shall be replaceable independently of other components

☒ ☐

Batteries shall be fused for short circuit protection

☒ ☐

Batteries shall be protected from overheating by means of a thermocouple sensor

☒ ☐

**ITEM #4 - 48" x 24" SOLAR POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL
(CONT'D)****COMPLIANCE****YES** **NO****BATTERY: (Cont'd)**

Batteries shall have the following dimensions:

Grouped: 2.66" H X 2.66" W X 2.78" D

☐ ☒

Stacked: 1.34" H X 1.34" W X 10.6" D

☐ ☒

Flatpack: 5.24" H X 2.68" W X 0.67" D

☐ ☒**WARRANTY:**

Manufacturer shall offer (at minimum) one (1) year of unconditional warranty against all defects in material and workmanship.

☒ ☐**OPTIONS:****4A – Steel Sign Post, As Specified****Description:**

Nucor RIB-BAK U-Channel Sign Support, galvanized (or approved equal).

☒ ☐**Measurements:**

10' length

☒ ☐

3-1/16" width

☒ ☐

3/8" holes on 1" centers

☒ ☐

2.5 lbs/ft linear weight

☒ ☐**Materials:**

Mounting hardware shall be Stainless Steel 5/16"

☒ ☐**4B - Battery For Solar-Powered LED Sign Assembly, As Specified****Description:**

6V, 14 Ah nickel metal hydride (NiMH) battery pack compatible with TAPCO® Blinkersigns®.

☐ ☒**Materials:**

Batteries shall be sealed in a plastic film to provide resistance to moisture and corrosion.

☐ ☒**Battery:**

Batteries shall not weigh more than 1.8 lbs.

☒ ☐

Batteries shall have a waterproof connection

☒ ☐

Batteries shall be sealed and spill-proof

☒ ☐

Batteries shall have an in-line power connector

☒ ☐

Batteries shall be replaceable independently of other components

☒ ☐

Batteries shall be fused for short circuit protection

☒ ☐

Batteries shall be protected from overheating by means of a thermocouple sensor

☒ ☐

ITEM #4 - 48" x 24" SOLAR POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL (CONT'D)**COMPLIANCE****YES** **NO****OPTIONS: (CONT'D)****4B - Battery For Solar-Powered LED Sign Assembly, As Specified (CONT'D)****Battery: (Cont'd)**

Batteries shall have the following dimensions:

Grouped: 2.66" H X 2.66" W X 2.78" D

☐ ☒

Stacked: 1.34" H X 1.34" W X 10.6" D

☐ ☒

Flatpack: 5.24" H X 2.68" W X 0.67" D

☐ ☒**Operation:**

Batteries shall remain operational between the temperatures of -40°F and 176°F (-40°C and 80°C), and shall utilize overheat protection.

☒ ☐**Electrical:**

All battery connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐**4C - Solar Panel For Solar-Powered LED Sign Assembly, As Specified****Description:**

Solar panel compatible with TAPCO® Blinkersigns® and of the correct size and parameters as necessary to maintain operation of a solar-powered LED sign assembly in the Ocean County Region.

☐ ☒**Mounting:**

The solar panel assembly shall be mounted securely to the sign assembly.

☐ ☒

All panels shall be mounted to an aluminum plate and bracket at an angle of 45° to 60°.

☒ ☐**Hardware:**

All fasteners used shall be anti-vandal.

☒ ☐**Electrical:**

Wire used shall conform to military specification MIL-W-16878D, Type D, vinyl nylon jacket.

☒ ☐

All solar panel connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐

ITEM #5 - 24" x 30" SOLAR POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL

COMPLIANCE

YES **NO**

DESCRIPTION:

Solar Powered and fully self-contained sign assembly conforming to the U.S. Department of Transportation Federal Highway Administration 2009 revision 2 May 2012 Manual on Uniform Traffic Control Devices section 2A.08 on retro reflectivity and illumination.

☒ ☐

MATERIALS:

The assembly shall include the following items:

SIGN:

Sign blanks shall be .080" gauge aluminum

☒ ☐

Sheeting shall be 3M DG Type IX or approved equal, with anti-graffiti overlay

☒ ☐

Sign assembly shall use anti-vandal fastener to mount components to sign and sign for fixture

☒ ☐

48" Signs shall have four (4) holes punched to allow dual post mounting and horizontal install

☒ ☐

Mounting hardware shall be Stainless Steel 5/16"

☒ ☐

LED:

Sign assembly shall utilize high-power 1W LEDs that provide a maximum light intensity of up to 600,000 mcd (millicandelas) with a viewing angle of 20 degrees.

☐ ☒

The sign faces shall have a color and minimum number of LEDs as noted below:

	<u>SIGN</u>	<u>LED Color</u>	<u>Minimum Number</u>		
Speed Limit (blank) 24" x 30" (Facing) Black on White	R2-1	White	8	☒	☐
Each LED shall be sealed in a heat-dissipating plastic enclosure to provide resistance to weather and vibration.				☒	☐
Each LED enclosure shall be mounted to the sign in a 1" hole and ultrasonically welded or mechanically fastened to the sign assembly.				☒	☐
All LEDs shall be wired in strings to activate simultaneously (as per MUTCD standard).				☒	☐
All wire used shall conform to military specification MIL-W-16878D, Type D, vinyl nylon jacket.				☒	☐
Wiring shall be covered and secured to the sign assembly in a weather resistant enclosure.				☒	☐
All LED connectors shall conform to Ingress Protection IP-65 rating or better.				☒	☐

ITEM #5 - 24" x 30" SOLAR POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL
(CONT'D)**COMPLIANCE****YES** **NO****SOLAR PANEL:**

Solar panels shall be sized appropriately so as to maintain the battery sufficiently to ensure operation in the Ocean County Region.

☒ ☐

All panels shall be mounted to an aluminum plate and bracket at an angle of 45° to 60°.

☒ ☐

All fasteners used shall be anti-vandal.

☒ ☐

Wire used shall conform to military specification MIL-W-16878D, Type D, vinyl nylon jacket.

☒ ☐

The solar panel assembly shall be mounted securely to the sign assembly.

☐ ☒

All solar panel connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐**CONTROL CIRCUIT:**

Control circuit shall have the capability of independently flashing dual outputs.

☒ ☐

Flashing output shall be 50 to 60 flashes per minute with 100 ms duration on time.

Outputs shall reach the output current as programmed for the duration of the 100 ms pulse.

☒ ☐

Output current shall be individually programmable for daytime and nighttime operation for the purpose of adjusting to ambient lighting conditions. Mode will automatically be determined by solar panel charge input.

☒ ☐

Control circuit covering shall be waterproof and anti-vandal.

☒ ☐

Control circuit shall remain operational between the temperatures of -40°F and 176°F.

☒ ☐

All circuit connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐**BATTERY:**

Battery packs shall be 4.8V, 14 Ah nickel metal hydride (NiMH).

☐ ☒

Batteries shall be sealed in a plastic film to provide resistance to moisture and corrosion.

☐ ☒

Batteries shall remain operational between the temperatures of -40°F and 176°F, and shall utilize overheat protection.

☒ ☐

All battery connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐

Batteries shall not weigh more than 1.8 lbs.

☒ ☐

Batteries shall have a waterproof connection

☒ ☐

Batteries shall be sealed and spill-proof

☒ ☐

Batteries shall have an in-line power connector

☒ ☐

Batteries shall be replaceable independently of other components

☒ ☐

Batteries shall be fused for short circuit protection

☒ ☐

Batteries shall be protected from overheating by means of a thermocouple sensor

☒ ☐

ITEM #5 - 24" x 30" SOLAR POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL
(CONT'D)

COMPLIANCE
YES NO

BATTERY: (Cont'd)

Batteries shall have the following dimensions:

Grouped: 2.66" H X 2.66" W X 2.78" D

☐ ☒

Stacked: 1.34" H X 1.34" W X 10.6" D

☐ ☒

Flatpack: 5.24" H X 2.68" W X 0.67" D

☐ ☒

WARRANTY:

Manufacturer shall offer (at minimum) one (1) year of unconditional warranty against all defects in material and workmanship.

☒ ☐

OPTIONS:

5A – Steel Sign Post, As Specified

Description:

Nucor RIB-BAK U-Channel Sign Support, galvanized (or approved equal).

☒ ☐

Measurements:

10' length

☒ ☐

3-1/16" width

☒ ☐

3/8" holes on 1" centers

☒ ☐

2.5 lbs/ft linear weight

☒ ☐

Materials:

Mounting hardware shall be Stainless Steel 5/16"

☒ ☐

5B - Battery For Solar-Powered LED Sign Assembly, As Specified

Description:

6V, 14 Ah nickel metal hydride (NiMH) battery pack compatible with TAPCO® Blinkersigns®.

☐ ☒

Materials:

Batteries shall be sealed in a plastic film to provide resistance to moisture and corrosion.

☐ ☒

Battery:

Batteries shall not weigh more than 1.8 lbs.

☒ ☐

Batteries shall have a waterproof connection

☒ ☐

Batteries shall be sealed and spill-proof

☒ ☐

Batteries shall have an in-line power connector

☒ ☐

Batteries shall be replaceable independently of other components

☒ ☐

Batteries shall be fused for short circuit protection

☒ ☐

ITEM #5 - 24" x 30" SOLAR POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL (CONT'D)**COMPLIANCE****YES** **NO****OPTIONS (Cont'd)****5B - Battery For Solar-Powered LED Sign Assembly, As Specified (Cont'd)**

Batteries shall be protected from overheating by means of a thermocouple sensor

☒ ☐

Batteries shall have the following dimensions:

Grouped: 2.66" H X 2.66" W X 2.78" D

☐ ☒

Stacked: 1.34" H X 1.34" W X 10.6" D

☐ ☒

Flatpack: 5.24" H X 2.68" W X 0.67" D

☐ ☒**Operation:**

Batteries shall remain operational between the temperatures of -40°F and 176°F (-40°C and 80°C), and shall utilize overheat protection.

☒ ☐**Electrical:**

All battery connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐**5C - Solar Panel For Solar-Powered LED Sign Assembly, As Specified****Description:**

Solar panel compatible with TAPCO® Blinkersigns® and of the correct size and parameters as necessary to maintain operation of a solar-powered LED sign assembly in the Ocean County Region.

☒ ☐**Mounting:**

The solar panel assembly shall be mounted securely to the sign assembly.

☐ ☒

All panels shall be mounted to an aluminum plate and bracket at an angle of 45° to 60°.

☒ ☐**Hardware:**

All fasteners used shall be anti-vandal.

☒ ☐**Electrical:**

Wire used shall conform to military specification MIL-W-16878D, Type D, vinyl nylon jacket.

☒ ☐

All solar panel connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐

ITEM #6 - 30" x 36" SOLAR POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL

COMPLIANCE
YES **NO**

DESCRIPTION:

Solar Powered and fully self-contained sign assembly conforming to the U.S. Department of Transportation Federal Highway Administration 2009 revision 2 May 2012 Manual on Uniform Traffic Control Devices section 2A.08 on retro reflectivity and illumination.

☒ ☐

MATERIALS:

The assembly shall include the following items:

Sign blanks shall be .080" gauge aluminum

☒ ☐

Sheeting shall be 3M DG Type IX or approved equal, with anti-graffiti overlay

☒ ☐

Sign assembly shall use anti-vandal fastener to mount components to sign and sign for fixture

☒ ☐

Mounting hardware shall be Stainless Steel 5/16"

☒ ☐

LED:

Sign assembly shall utilize high-power 1W LEDs that provide a maximum light intensity of up to 600,000 mcd (millicandelas) with a viewing angle of 20 degrees.

☐ ☒

The sign faces shall have a color and minimum number of LEDs as noted below:

	<u>SIGN</u>	<u>LED Color</u>	<u>Minimum Number</u>		
Speed Limit (blank) 30" x 36" (Facing) Black on White	R2-1	White	8	☒	☐
Each LED shall be sealed in a heat-dissipating plastic enclosure to provide resistance to weather and vibration.				☒	☐
Each LED enclosure shall be mounted to the sign in a 1" hole and ultrasonically welded or mechanically fastened to the sign assembly.				☐	☒
All LEDs shall be wired in strings to activate simultaneously (as per MUTCD standard).				☒	☐
All wire used shall conform to military specification MIL-W-16878D, Type D, vinyl nylon jacket.				☒	☐
Wiring shall be covered and secured to the sign assembly in a weather resistant enclosure.				☒	☐
All LED connectors shall conform to Ingress Protection IP-65 rating or better.				☒	☐

SOLAR PANEL:

Solar panels shall be sized appropriately so as to maintain the battery sufficiently to ensure operation in the Ocean County Region.

☒ ☐

All panels shall be mounted to an aluminum plate and bracket at an angle of 45° to

☒ ☐

Reduced on: May 27, 2026

Adopted on: May 27, 2026

All fasteners used shall be anti-vandal.

☒ ☐

ITEM #6 - 30" x 36" SOLAR POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL (CONT'D)

	<u>COMPLIANCE</u>	
	<u>YES</u>	<u>NO</u>
<u>SOLAR PANEL: (CONT'D)</u>		
Wire used shall conform to military specification MIL-W-16878D, Type D, vinyl nylon jacket.	☒	☐
The solar panel assembly shall be mounted securely to the sign assembly.	☐	☒
All solar panel connectors shall conform to Ingress Protection IP-65 rating or better.	☒	☐
<u>CONTROL CIRCUIT:</u>		
Control circuit shall have the capability of independently flashing dual outputs.	☒	☐
Flashing output shall be 50 to 60 flashes per minute with 100 ms duration on time. Outputs shall reach the output current as programmed for the duration of the 100 ms pulse.	☒	☐
Output current shall be individually programmable for daytime and nighttime operation for the purpose of adjusting to ambient lighting conditions. Mode will automatically be determined by solar panel charge input.	☒	☐
Control circuit covering shall be waterproof and anti-vandal.	☒	☐
Control circuit shall remain operational between the temperatures of -40°F and 176°F.	☒	☐
All circuit connectors shall conform to Ingress Protection IP-65 rating or better.	☒	☐
<u>BATTERY:</u>		
Battery packs shall be 4.8V, 14 Ah nickel metal hydride (NiMH).	☐	☒
Batteries shall be sealed in a plastic film to provide resistance to moisture and corrosion.	☐	☒
Batteries shall remain operational between the temperatures of -40°F and 176°F, and shall utilize overheat protection.	☒	☐
All battery connectors shall conform to Ingress Protection IP-65 rating or better.	☒	☐
Batteries shall not weigh more than 1.8 lbs.	☐	☒
Batteries shall have a waterproof connection	☒	☐
Batteries shall be sealed and spill-proof	☒	☐
Batteries shall have an in-line power connector	☒	☐
Batteries shall be replaceable independently of other components	☒	☐
Batteries shall be fused for short circuit protection	☒	☐
Batteries shall be protected from overheating by means of a thermocouple sensor	☒	☐
Batteries shall have the following dimensions:		
Grouped: 2.66" H X 2.66" W X 2.78" D	☐	☒
Stacked: 1.34" H X 1.34" W X 10.6" D	☐	☒
Flatpack: 5.24" H X 2.68" W X 0.67" D	☐	☒

WARRANTY:

Manufacturer shall offer (at minimum) one (1) year of unconditional warranty against all defects in material and workmanship.

Introduced on: May 27, 2026
 Adopted on: May 27, 2026
 Official Resolution#: 2026000658

☒ ☐

ITEM #6 - 30" x 36" SOLAR POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL (CONT'D)

COMPLIANCE

YES **NO**

OPTIONS:

6A – Steel Sign Post, As Specified

Description:

Nucor RIB-BAK U-Channel Sign Support, galvanized (or approved equal).

☒ ☐

Measurements:

10' length

☒ ☐

3-1/16" width

☒ ☐

3/8" holes on 1" centers

☒ ☐

2.5 lbs/ft linear weight

☒ ☐

Materials:

Mounting hardware shall be Stainless Steel 5/16"

☒ ☐

6B - Battery For Solar-Powered LED Sign Assembly, As Specified

Description:

6V, 14 Ah nickel metal hydride (NiMH) battery pack compatible with TAPCO® Blinkersigns®.

☐ ☒

Materials:

Batteries shall be sealed in a plastic film to provide resistance to moisture and corrosion.

☒ ☐

Battery:

Batteries shall not weigh more than 1.8 lbs.

☐ ☒

Batteries shall have a waterproof connection

☒ ☐

Batteries shall be sealed and spill-proof

☒ ☐

Batteries shall have an in-line power connector

☒ ☐

Batteries shall be replaceable independently of other components

☒ ☐

Batteries shall be fused for short circuit protection

☒ ☐

Batteries shall be protected from overheating by means of a thermocouple sensor

☒ ☐

Batteries shall have the following dimensions:

Grouped: 2.66" H X 2.66" W X 2.78" D

☐ ☒

Stacked: 1.34" H X 1.34" W X 10.6" D

☐ ☒

Flatpack: 5.24" H X 2.68" W X 0.67" D

☐ ☒

Operation:

Batteries shall remain operational between the temperatures of -40°F and 176°F (-40°C and 80°C), and shall utilize overheat protection.

☒ ☐

Electrical:

All battery connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐

**ITEM #6 - 30" x 36" SOLAR POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL
 (CONT'D)**

COMPLIANCE

YES **NO**

OPTIONS: (CONT'D)

6C - Solar Panel For Solar-Powered LED Sign Assembly, As Specified

Description:

Solar panel compatible with TAPCO® Blinkersigns® and of the correct size and parameters as necessary to maintain operation of a solar-powered LED sign assembly in the Ocean County Region.

☐ ☒

Mounting:

The solar panel assembly shall be mounted securely to the sign assembly.

☐ ☒

All panels shall be mounted to an aluminum plate and bracket at an angle of 45° to 60°.

☒ ☐

Hardware:

All fasteners used shall be anti-vandal.

☒ ☐

Electrical:

Wire used shall conform to military specification MIL-W-16878D, Type D, vinyl nylon jacket.

☒ ☐

All solar panel connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐

ITEM #7 - SOLAR SPEED RADAR SIGN, 12", TRAFFIC LOGIX SAFEFACE EVOLUTION 12, AS SPECIFIED, OR EQUAL

	<u>COMPLIANCE</u>	
	<u>YES</u>	<u>NO</u>
<u>DESCRIPTION:</u>		
Changeable message sign which displays speed of oncoming vehicles. Includes MUTCD-compliant "YOUR SPEED" sign (black legend on yellow background). Sign shall warn drivers who exceed designated threshold speed.	☒	☐
<u>SPEED DISPLAY:</u>		
Individual digits within display shall be 12" h x 6.4" w, and each digit shall be comprised of a matrix of no fewer than 196 yellow LEDs per digit; total 936 yellow LEDs.	☒	☐
The LEDs shall be displayed on a black background.	☒	☐
The yellow digits shall have a viewing angle at 50% IV of 30° and a partial flux (brightness) of 9000-22400 Ev, [lux]/LED.	☒	☐
Display face shall be constructed of non-glare UV stabilized polycarbonate.	☒	☐
Display shall have an operating temperature range of -40°F to 185°F with 95% humidity non-condensing. (-20°F for Bluetooth communication)	☒	☐
Speed display size shall be maximum 17.25" (h) x 23" (w) x 5.625" (d).	☒	☐
The speed display shall be capable of displaying speeds in miles per hour and ranging from 3 – 99.	☒	☐
There shall be a conformal coating on all circuit boards	☒	☐
There shall be a built in ambient light sensing and automatic brightness control.	☒	☐
<u>SIGN:</u>		
Sign shall conform to the 2009 Federal Highway MUTCD section 2A.08 on retroreflectivity and illumination.	☒	☐
Sign shall measure at least 29" h x 23" w.	☒	☐
Sign blanks shall be aluminum.	☒	☐
Sheeting used shall be 3M DG3 diamond grade, or approved equal, with anti-graffiti overlay.	☒	☐
The sign shall measure 29.0" (h) x 23.0" (w) x 5.625" (d) and display the message "YOUR SPEED" on two (2) lines.	☒	☐
Sign weight with speed radar shall be a maximum of 20 pounds.	☒	☐
Mounting hardware shall be Stainless Steel 5/16"	☒	☐

ITEM #7 - SOLAR SPEED RADAR SIGN, 12", TRAFFIC LOGIX SAFEFACE EVOLUTION 12, AS SPECIFIED, OR EQUAL (CONT'D)**COMPLIANCE****YES** **NO****PROGRAMMING:**

There shall be 24/7 365 day programming and scheduling.	☒	☐
The unit shall be capable of display On/Stealth Modes.	☒	☐
The unit shall display the closest/fastest vehicle speed.	☒	☐
The unit shall have a digit flashing speed threshold.	☒	☐
The following are the flashing speeds for the LEDs: Fast 1.5 Hz, Medium 1 Hz, and Slow 0.75 Hz.	☒	☐
The unit shall be capable of collecting and storing traffic data by location.	☒	☐
The unit shall capture traffic data when in Stealth Mode.	☒	☐
The data shall be downloaded via a wireless connection.	☒	☐
The program shall be capable of statistical reporting and charts.	☒	☐
The program shall be capable of compiling the reports as summaries, weekly reports, period comparison reports, or full custom reports and charts.	☒	☐
The program shall be capable of reporting the following parameters: average vehicle count, total vehicle count, average speed, average number of speed violations, total number of speed violations, minimum/maximum speed, 85th percentile speed.	☒	☐
The reports shall print directly and exported into CSV, MS Excel, Adobe Acrobat PDF and HTML formats.	☒	☐

SOLAR PANEL:

Solar panels shall be sized appropriately so as to maintain the battery sufficiently.	☒	☐
All panels shall be mounted to an aluminum plate and bracket at an angle of 45° to 60°.	☒	☐
All fasteners used shall be anti-vandal.	☒	☐
Wire used shall conform to military specification MIL-W-16878D, Type D, vinyl nylon jacket.	☒	☐
The solar panel assembly shall be mounted securely to the sign assembly.	☒	☐
All solar panel connectors shall conform to Ingress Protection IP-65 rating or better.	☒	☐
The solar panel shall be a 50W or 90W solar panel.	☒	☐

ITEM #7 - SOLAR SPEED RADAR SIGN, 12", TRAFFIC LOGIX SAFEPLACE EVOLUTION 12, AS SPECIFIED, OR EQUAL (CONT'D)

	<u>COMPLIANCE</u>	
	<u>YES</u>	<u>NO</u>
<u>ENCLOSURE:</u>		
The enclosure shall be vandal resistant and have a lightweight polymer.	☒	☐
The enclosure shall have a matte black front.	☐	☒
The enclosure shall have a light gray body.	☐	☒
The enclosure shall be weatherproof and be NEMA 4X-12 and IP65 compliant.	☐	☒
The enclosure shall be non-sealed and ventilated.	☒	☐
<u>RADAR:</u>		
The unit shall use an internal radar that is Doppler and FCC approved.	☒	☐
The radar RF out shall be 5 mW maximum.	☒	☐
The radar f-center shall be 24.125 GHz or 24.200 GHz.	☒	☐
The radar shall have a maximum pickup distance of 400 feet.	☒	☐
The beam angle shall be 24° (vertical) x 12° (horizontal).	☒	☐
The radar beam polarization shall be linear.	☒	☐
The radar shall have CE Mark.	☒	☐
<u>BATTERY:</u>		
The sign shall have Lithium-ion batteries with a weight of 4 pounds.	☐	☒
The universal mounting bracket system shall come with a sign bracket (2 pounds) and a pole bracket (5 pounds).	☒	☐
The power input shall be 100~240V AC @ 150 mA, 12V DC (11-14.5V @ 1A).	☒	☐
The power input shall be capable of wireless battery charge monitoring via software interface.	☐	☒
<u>COMMUNICATIONS:</u>		
The device shall be Bluetooth Capable.	☒	☐
<u>ASSEMBLY:</u>		
Assembly shall be capable of mounting to pole, timber post, or u-channel.	☒	☐
Mounting hardware shall be tamper-resistant.	☒	☐

ITEM #7 - SOLAR SPEED RADAR SIGN, 12", TRAFFIC LOGIX SAFEPLACE EVOLUTION 12, AS SPECIFIED, OR EQUAL (CONT'D)**COMPLIANCE**
YES **NO****WARRANTY:**

Manufacturer shall offer (at minimum) one (1) year of unconditional warranty against all defects in material and workmanship.

☒ ☐

Manufacturer shall offer (at minimum) ten (10) years warranty on LEDs.

☒ ☐

Manufacturer shall offer (at minimum) two (2) year warranty on the sign.

☒ ☐

Manufacturer shall offer (at minimum) one (1) year warranty on the batteries.

☒ ☐

ITEM # 8 - SOLAR SPEED RADAR SIGN, 15", TRAFFIC LOGIX SAFEPLACE 450 FULL RADAR SPEED SIGN, AS SPECIFIED, OR EQUAL**DESCRIPTION:**

Changeable message sign which displays speed of oncoming vehicles. Includes MUTCD – compliant "YOUR SPEED" sign (black legend on yellow background). Sign shall warn drivers who exceed designated threshold speed.

☒ ☐

SPEED RADAR SIGN:

The assembly shall include the following items:

The Speed Radar Sign Digits shall be 15.0"(h)x8.0"(w) with 112 yellow LEDs per digit.

☒ ☐

The "YOUR SPEED" text on the speed radar sign shall be 6" H and on two (2) lines.

☒ ☐

The full Speed Radar Sign size shall be 40.0" H x 30.0" W x 3.5" D.

☒ ☐

The sign weight without the "YOUR SPEED" sign and with the solar power panel and bracket shall be 20 pounds *maximum*.

☐ ☒

The sign shall come with 4 cell lithium ion battery (4 lbs max).

☐ ☒

The sign shall come with a universal mounting bracket system including the sign bracket (2 lbs) and pole bracket (5 lbs).

☒ ☐

The speed radar sign shall measure the speed in miles per hour (MPH).

☒ ☐

The speed radar sign shall have an aluminum protective cover 0.1875" D.

☒ ☐

The sign shall have yellow high-intensity prismatic reflective sheeting on the sign face with black colored text in MUTCD approved colors and format.

☒ ☐

The operating temperature shall be -40°F to 185°F *minimum*.

☒ ☐

The sign shall have a built in ambient light sensor.

☒ ☐

The sign shall have a wireless battery charge monitor.

☒ ☐

POWER SOURCE:

Introduced on: May 27, 2026

Approved on: May 27, 2026
The sign shall have be solar powered.

Official Resolution#: 2026000658

☒ ☐

ITEM #8 - SOLAR SPEED RADAR SIGN, 15", TRAFFIC LOGIX SAFE PACE 450 FULL RADAR SPEED SIGN, AS SPECIFIED, OR EQUAL (CONT'D)

	<u>COMPLIANCE</u>	
	<u>YES</u>	<u>NO</u>
<u>RADAR:</u>		
The radar sign shall have a ten (10) year warranty on the LEDs.	☒	☐
The internal radar shall be Doppler (FCC approved).	☒	☐
The radar RF out shall be 5mW maximum.	☒	☐
The radar f-center shall be 24.125 GHz center $\pm$ 25 MHz.	☒	☐
The radar pick-up distance shall go up to 1,200 feet <i>minimum</i> .	☒	☐
The radar beam angle shall be 11°x11°.	☒	☐
The radar beam polarization shall be linear.	☒	☐
The FCC ID for the radar shall be TIADR1500.	☒	☐
<u>DISPLAY:</u>		
LED Digits shall have 224 yellow LED, 23°, 5mm, luminous intensity (5,680-8,200 mcd/LED).	☒	☐
The display shall have an ambient light sensor and automatic brightness adjuster.	☒	☐
<u>ENCLOSURE:</u>		
The enclosure shall be 12 gauge aluminum with flat black powder coated front.	☐	☒
The body of the enclosure shall be light gray powder coated.	☐	☒
The enclosure shall be weather proof, non-sealed, and ventilated.	☒	☐
The enclosure shall be NEMA 4X-12 and IP65 level compliant.	☐	☒
<u>MOUNTING:</u>		
The brackets shall be theft resistant.	☒	☐
The sign shall lock into the bracket with a key.	☒	☐
The universal mounting bracket system shall have the following options: circular, square, and telspar poles.	☒	☐
The mounting system shall come with banding brackets.	☒	☐
<u>COMMUNICATIONS:</u>		
The system shall be both WiFi and Bluetooth 4.0 compatible.	☐	☒
<u>PROGRAMMING:</u>		
Safe Pace Pro management software or approved equal shall be utilized.	☒	☐
There shall be 24 hours a day, 7 days a week, 365 days a year unlimited programming and scheduling.	☒	☐

ITEM #8 - SOLAR SPEED RADAR SIGN, 15", TRAFFIC LOGIX SAFE PACE 450 FULL RADAR SPEED SIGN, AS SPECIFIED, OR EQUAL (CONT'D)

	<u>COMPLIANCE</u>	
	<u>YES</u>	<u>NO</u>
<u>DISPLAY SETTINGS:</u>		
The display shall have both 'ON' and 'Stealth Mode' settings.	☒	☐
In stealth mode, the speed will not be displayed and the data will be collected.	☒	☐
The display will be capable of a minimum speed and maximum speed.	☒	☐
The display will be capable of flashing the digits when the speed is measured above the selected speed.	☒	☐
<u>DATA COLLECTION:</u>		
Traffic data shall be collected and stored by location.	☒	☐
Traffic data shall be downloaded through a wireless connection.	☒	☐
The program shall be capable of statistical reports and charts.	☒	☐
The following reports shall be compiled: summary reports, weekly reports, period comparison reports, and customizable reports.	☒	☐
The following shall be the reporting parameters:	☒	☐
• average vehicle count • total vehicle count • average speed • average number of speed violations • total number of speed violations • minimum and maximum speed • 85th percentile speed		
The reports shall be capable of printing directly from the program and exported into CSV format, MS Excel, Adobe Acrobat PDF, and HTML.	☒	☐
The charts shall be capable of printing directly from the program and Adobe Acrobat PDF format.	☒	☐
<u>SOLAR PANEL:</u>		
The solar panel power output shall be 20 W.	☐	☒
The solar panel operation temperature range shall be -40°C to 85°C <i>minimum</i> .	☒	☐
The solar panel shall be composed of laminate: glass, EVA, TPT (tedlar/pet/tedlar), or TPE.	☐	☒
The front side of the solar panel shall have high-transmission 3.2mm tempered glass.	☐	☐
The back side of the solar panel shall be made of wither TPT or TPE.	☐	☒
The solar panel frame shall be clear anodized aluminum.	☒	☐
The solar panel shall be output to a junction box.	☒	☐

COMPLIANCE PAGES – SOLAR POWERED LED AND SPEED RADAR SIGNS

ITEM #9 – STEEL SIGN POST, AS SPECIFIED, OR EQUAL**COMPLIANCE****YES** **NO****DESCRIPTION:**

Nucor RIB-BAK U-Channel Sign Support, galvanized, without breakaways (or approved equal)

☒ ☐**MEASUREMENTS:**

10' length

☒ ☐

3-1/16" width

☒ ☐

3/8" holes on 1" centers

☒ ☐

2.5 lbs/ft linear weight

☒ ☐**Materials:**

Mounting hardware shall be Stainless Steel 5/16"

☒ ☐**ITEM #10 - BATTERY FOR SOLAR-POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL****DESCRIPTION:**

6V, 14 Ah nickel metal hydride (NiMH) battery pack compatible with TAPCO® Blinkersigns®.

☐ ☒**MATERIALS:**

Batteries shall be sealed in a plastic film to provide resistance to moisture and corrosion.

☐ ☒**BATTERY:**

Batteries shall not weigh more than 1.8 lbs.

☒ ☐

Batteries shall have a waterproof connection

☒ ☐

Batteries shall be sealed and spill-proof

☒ ☐

Batteries shall have an in-line power connector

☒ ☐

Batteries shall be replaceable independently of other components

☒ ☐

Batteries shall be fused for short circuit protection

☒ ☐

Batteries shall be protected from overheating by means of a thermocouple sensor

☒ ☐

Batteries shall have the following dimensions:

Grouped: 2.66" H X 2.66" W X 2.78" D

☐ ☒

Stacked: 1.34" H X 1.34" W X 10.6" D

☐ ☒

Flatpack: 5.24" H X 2.68" W X 0.67" D

☐ ☒**OPERATION:**

Batteries shall remain operational between the temperatures of -40°F and 176°F (-40°C and 80°C), and shall utilize overheat protection.

☒ ☐**ELECTRICAL:**

All battery connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐

ITEM #11 - SOLAR PANEL FOR SOLAR-POWERED LED SIGN ASSEMBLY, AS SPECIFIED, OR EQUAL**COMPLIANCE**
YES **NO****DESCRIPTION:**

Solar panel compatible with TAPCO® Blinkersigns® and of the correct size and parameters as necessary to maintain operation of a solar-powered LED sign assembly in the Ocean County Region.

☐ ☒

MOUNTING:

The solar panel assembly shall be mounted securely to the sign assembly.
All panels shall be mounted to an aluminum plate and bracket at an angle of 45° to 60°.

☐ ☒
☒ ☐

HARDWARE:

All fasteners used shall be anti-vandal.

☒ ☐

ELECTRICAL:

Wire used shall conform to military specification MIL-W-16878D, Type D, vinyl nylon jacket.

☒ ☐

All solar panel connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐

ITEM #12 - SOLAR-POWERED LED PEDESTRIAN CROSSING WARNING SYSTEM WITH PUSH BUTTONS, AS SPECIFIED OR EQUAL**DESCRIPTION:**

Fully self-contained Solar-Powered LED Pedestrian Crossing Warning System, including an LED-enhanced pedestrian crossing sign assembly (conforming to the 2009 Federal Highway MUTCD section 2A.08 on retroreflectivity and illumination). Each system shall consist of two (2) solar-powered LED pedestrian crossing signs, two (2) cabinets, two (2) pedestrian push button assemblies, two (2) sign mounting kits, two (2) wireless controller kits, and all appurtenances incidental to the Solar-Powered LED Pedestrian Crossing Warning System.

☒ ☐

MATERIAL:

The system shall include the following items:

SIGN:

MUTCD compliant Pedestrian warning sign type W11-2. 36" x 36"

☒ ☐

Sign blanks shall be .080" gauge aluminum.

☒ ☐

Sheeting used shall be 3M DG3 diamond grade, or approved equal, with anti-graffiti overlay.

☒ ☐

Sign assembly shall use anti-vandal fasteners to mount components to sign and sign to fixture.

☒ ☐

Mounting hardware shall be Stainless Steel 5/16"

☒ ☐

ITEM #12 - SOLAR-POWERED LED PEDESTRIAN CROSSING WARNING SYSTEM WITH PUSH BUTTONS, AS SPECIFIED OR EQUAL (CONT'D)**COMPLIANCE**
YES **NO****LEDS:**

Sign assembly shall utilize a minimum of eight (8) high-power 1 W LEDs that provide a maximum light intensity of up to 600,000 mcd (millicandelas) with a viewing angle of 20°.

☒ ☐

LEDs shall be amber in color.

☒ ☐

Each LED shall be sealed in a heat-dissipating plastic enclosure to provide resistance to weather and vibration.

☒ ☐

Each LED enclosure shall be mounted to the sign in a 1" hole and ultrasonically welded or mechanically fastened to the sign assembly.

☒ ☐

All LEDs shall be wired in strings to activate simultaneously (as per MUTCD standard).

☒ ☐

All wire used shall conform to military specification MIL-W-16878D, Type D, vinyl nylon jacket.

☒ ☐

Wiring shall be covered and secured to the sign assembly in a weather resistant enclosure.

☒ ☐

All LED connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐

SOLAR PANEL:

Solar panels shall be sized appropriately so as to maintain the battery sufficiently to ensure operation in the Ocean County Region.

☒ ☐

All panels shall be mounted to an aluminum plate and bracket at an angle of 45° to 60°.

☒ ☐

All fasteners used shall be anti-vandal.

☒ ☐

Wire used shall conform to military specification MIL-W-1687D, Type D, vinyl nylon jacket.

☒ ☐

The solar panel assembly shall be mounted securely to the sign assembly.

☒ ☐

All solar panel connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐

PUSH BUTTON:

Sign assembly shall include a Polara Bulldog Push Button (or approved Equal), yellow in color and with an LED for visual confirmation of activation.

☒ ☐

Push button connectors shall conform to Ingress Protection, IP-65 rating or better.

☒ ☐

CONTROL CIRCUIT:

Control circuit shall have the capability of independently flashing dual outputs.

☒ ☐

Flashing output shall be 50 to 60 flashes per minute with 100 ms duration on time.

Outputs shall reach the output current as programmed for the duration of the 100 ms pulse.

☒ ☐

Output current shall be individually programmable for daytime and nighttime operation for the purpose of adjusting to ambient lighting conditions. Mode will automatically be determined by solar panel charge input.

☒ ☐

Control circuit covering shall be waterproof and anti-vandal.

☒ ☐

ITEM #12 - SOLAR-POWERED LED PEDESTRIAN CROSSING WARNING SYSTEM WITH PUSH BUTTONS, AS SPECIFIED OR EQUAL (CONT'D)**COMPLIANCE**
YES **NO****CONTROL CIRCUIT: (CONT'D)**

Control circuit shall remain operational between the temperatures of -40°F and 176°F (-40°C and 80°C).

☒ ☐

All circuit connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐

BATTERY:

Battery packs shall be 4.8V, 14000 mAh nickel metal hydride (NiMH).

☐ ☒

Batteries shall be sealed in a plastic film to provide resistance to moisture and corrosion. Dimensions shall be 10.5" x 1.5" to be house in a 2-3/8" aluminum tube.

☐ ☒

Batteries shall remain operational between the temperatures of -40°F and 176°F (-40°C and 80°C), and shall utilize heat protection.

☒ ☐

All battery connectors shall conform to Ingress Protection IP-65 rating or better.

☒ ☐

WIRELESS COMMUNICATION:

Each system shall include a radio-control cabinet for communication with and synchronization within the system.

☒ ☐

Each sign assembly shall include a self-powered wireless transmitter / receiver for communication with the control cabinet.

☒ ☐

Transmitter units shall have a minimum operating range of 1000 ft (line of sight).

☐ ☐

WARRANTY:

Manufacturer shall offer (at minimum) one (1) year of unconditional warranty against all defects in material and workmanship.

☒ ☐