

Ocean County Board of Commissioners

OFFICE OF THE OCEAN COUNTY COMMISSIONERS

Director Joseph H. Vicari
Deputy Director Gary Quinn
Commissioner Barbara Jo Crea
Commissioner Virginia E. Haines
Commissioner John P. Kelly

101 Hooper Avenue Toms River, New Jersey 08754-2191 (732)929-2005 (732)505-1918

Board Meeting Agenda

Date: December 20, 2023 - 4:00 PM

Location: Administration Building

Room 119


101 Hooper Avenue Toms River, NJ 08754

Agenda: Awarding a Contract for the FURNISHING AND INSTALLATION OF ONE (1) DOUBLE CASCADIAN STYLE PRE-CAST VAULT RESTROOM BUILDING to West Bay Construction, Inc., the lowest qualified bidder. (B2023-207)

Official Resolution#			2023001835					
Meeting Date			12/20/2023					
Introduced Date			1	2/2	20/2	023	3	
Adopted Date			1	2/2	20/2	023	3	
Agenda Item			j-	4				
CAF#								
Purchase Req. #			B2023-207					
Result			Adopted					
COUNTY COMMISSIONER	PRES.	ABS.		MOVE	SEC	AYE	NAY	ABST.
Vicari	V					~		
Quinn	~					~		
Crea	V				V	~		
Haines	~					~		
Kelly	~			~		~		

I HEREBY CERTIFY THAT THIS DOCUMENT IS A TRUE, COMPLETE AND ACCURATE COPY OF THIS RESOLUTION, ADOPTED BY OCEAN COUNTY BOARD OF COMMISSIONERS, NJ AT THE MEETING REFERENCED THEREON

Clerk Of The Board



RESOLUTION

December 20, 2023

WHEREAS, on November 21, 2023, pursuant to legal advertisements therefor, sealed bids were received for the FURNISHING AND INSTALLATION OF ONE (1) DOUBLE CASCADIAN STYLE PRE-CAST VAULT RESTROOM BUILDING for the County of Ocean; and

WHEREAS, at the advertised time, responses was received from the following

bidders:

Name and Address of Bidder

West Bay Construction, Inc. 133 Pleasant Ave. Absecon, NJ 08201 (609) 380-7065

Scozzari Builders, Inc. 1891 North Olden Avenue Trenton, NJ 08638 (609) 989-1221

Name and Address of Bidder

George Koustas Ptg. & Constr., LLC 70 Beechwood Ave. West Long Branch, NJ 07764 (732) 571-1148

; and

WHEREAS, after the receipt and examination of same, the County Purchasing Agent has now recommended to this Board that the lowest qualified bid, according to specifications, namely that of, WEST BAY CONSTRUCTION, INC., be accepted.

NOW, THEREFORE, BE IT RESOLVED by the BOARD COMMISSIONERS of the COUNTY OF OCEAN, STATE OF NEW JERSEY, as follows:

1. The Director and Clerk of this Board are hereby authorized and directed to enter into a contract for the Furnishing and Installation of One (1) Double Cascadian Style Pre-Cast Vault Restroom Building. The contract shall be in effect from date of award through December 19, 2024 a period of one (1) year, or until delivery is complete unless otherwise stated. The County reserves the right to extend the term of the contract pursuant to N.J.S.A. 40A:11-15.

> WEST BAY CONSTRUCTION, INC. for two (2) items, to wit: A.

ITEM NOS. 1 and 1a.

For a Total Lump Sum Award (Item Nos. 1 and 1a) of \$147,500.00.

Introduced on Adopted on: Official Resolution#: 2023001835

December 20, 2023 December 20, 2023

Res-Pg:j.4-3 DECEMBER 20, 2023

- 2. The Department of Finance has certified that funds are available in Account No. 301-250-X116 in the amount of \$147,500.00 to cover this contract and the amount of the contract shall be encumbered against the said Appropriations.
- 3. The contract number must be placed on all papers, documents, invoices and vouchers pertaining to said contract, the number being B2023-207.
- 4. Be it further resolved that certified copies of this Resolution shall be made available to the County Auditor, County Director of Purchase, Department of Finance, County Parks Department and West Bay Construction Inc., the successful bidder.

Introduced on: Adopted on: Official Resolution#: 2023001835

PROPOSAL DOCUMENT REPORT Bid No. OCPK112123

FURNISHING AND INSTALLATION OF ONE (1) DOUBLE CASCADIAN STYLE PRE-CAST VAULT RESTROOM BUILDING

16. Acknowledgement of Submission of Forms from Current Bid Package*

Bidders shall complete all documents and acknowledge all terms included with the bid package. All documents should be from this bid package as forms change frequently and the most updated forms are provided in this specification. The forms must not be dated or executed prior to the date of advertising. Failure to follow these instructions is cause for rejection.

Confirmed

17. Submission of Bid Package*

By submitting a response to this solicitation, the Vendor understands and acknowledges that all required documents to this solicitation must be submitted and that failure to do so may be cause for rejection.

Bidder also understands that only one (1) bid submission shall be considered. Please DO NOT Submit a manual bid response. Submitting a manual response in addition to the electronic response is cause for rejection of your bid.

Confirmed

PRICE TABLES FURNISHING AND INSTALLATION OF ONE (1) DOUBLE CASCADIAN STYLE PRE-CAST VAULT RESTROOM BUILDING

Line Item	Description	Quantity	Unit of Measure	Unit Cost	Total	Mfr./Model:	Warranty Details:	Delivery, A.R.O.:	Comments:
1	Furnishing And Installation Of One (1) Double Cascadian Style Pre- Cast Vault Restroom Building at the Ocean County Golf Course at Atlantis, Little Egg Harbor, NJ, As Specified or Equal	1	LS	\$145,500.00	\$145,500.00	CXT Dbl. Cascadian	Standard 1 Yr	6-9 Mo. from Recietpt of approved Submittals	Excludes Electrical and Plumbing Work o services.
ALLOWANCE	<u> </u>					- min - cappane property		A min and the Highlighton has been reported to the second	<u> </u>

Introduced on:

December 20, 2023

official Resolution# 2023001835 REPOR

Bid - FURNISHING AND INSTALLATION OF ONE (1) DOUBLE CASCADIAN STYLE PRE-CAST VAULT RESTROOM BUILDING

PROPOSAL DOCUMENT REPORT Bid No. OCPK112123

FURNISHING AND INSTALLATION OF ONE (1) DOUBLE CASCADIAN STYLE PRE-CAST VAULT RESTROOM BUILDING

,	Line Item	Description	Quantity	Unit of Measure	Unit Cost	Total	Mfr./Model:	Warranty Details:	Delivery, A.R.O.:	Commonts
	1a	Allowance for Options/Accessories, As Needed	.1	LS	\$2,000.00	\$2,000.00			, ,	-
	TOTAL	<u> </u>		,		\$147,500.00				

Introduced on:

Adopted Ribposal December 12023001835
Official Resolution#: 2023001835
Bid - FURNISHING AND INSTALLATION OF ONE (1) DOUBLE CASCADIAN STYLE PRE-CAST VAULT RESTROOM BUILDING

COMPLIANCE PAGES FOR FURNISHING AND INSTALLATION OF ONE (1) DOUBLE CASCADIAN STYLE PRE-CAST VAULT RESTRECM

Page 1 of 4

ITEM #1 - FURNISHING AND INSTALLATION OF ONE (1) DOUBLE CASCADIAN STYLE PRE-CAST VAULT RESTROOM BUILDING AT THE OCEAN COUNTY GOLF COURSE AT ATLANTIS, LITTLE EGG HARBOR, NJ

		YES YES	CE NO
Specifications	· · · · · · · · · · · · · · · · · · ·	<u>I LWI</u>	110
Size:	Footprint 11'-11" x 14'- 4"		
	Building – 14'-4" x 7'-11 1/4" x 12' (to top of ridge)		
	Vault 13' 6" x 11' 11" x 4'-4"		
Roof:	Shall have a minimum thickness of 4.5" all concrete design with a minimum 7/12 pitch, designed to withstand 350lb. /per square foot of snow load and withstand the effects of 150 MPH (3 second gust) wind exposure.		<u>.</u>
<u>Floor:</u>	Color to be chosen by County. Shall be one pieces floor unit 5" all concrete, designed to withstand 400 lb. /square foot floor load. Floors shall be painted grey with a chemical	⊠ al	
	resistant urethane.		
Building:	Walls shall have a minimum thickness of 4", all concrete design, and withstand the effects of 150 MPH (3 second gust) wind exposure. The building shall have two (2) one-piece full length and width vault unit to		
	support the building, screen area and snow loads evenly.		
<u>Colored</u>		h .	
Concrete:	The same brand and type of color additive shall be used throughout the manufacturing process; and all ingredients shall be weighed and the mixing operation shall be adequate to ensure uniform dispersion of color. Toilet building roof panels, Color & Texture to be chosen by Count Building walls (exterior), Color & Texture to be chosen by County	ty	
	Screen Panels, Color & Texture to be chosen by County.	\boxtimes	
<u>Paint</u>	Interior Paint: Floors – Grey, chemical resistant urethane Walls & Ceiling, White, modified acrylic, water repellent penetrating stain followed by a clear acrylic anti-graffiti sealer.	⊠	
	Exterior Paint: Slab – Clear Sealer		
	Walls & Roof – Shall be a water repellent penetrating stain in the same colors as the walls or roof followed by a clear acrylic	v	e e
	anti-graffiti sealer.		
	Metal Surfaces (interior & exterior)		
Introduced on: Adopted on:	Shall be DTM ALKYD, or approved equal December 20, 2023 December 20, 2023		Ц

Official Resolution#: 2023001835

COMPLIANCE PAGES FOR FURNISHING AND INSTALLATION OF ONE (1) DOUBLE CASCADIAN STYLE PRE-CAST VAULT RESTROOM

BUILDING

Page 2 of 4

ITEM #1 - FURNISHING AND INSTALLATION OF ONE (1) DOUBLE CASCADIAN STYLE PRE-CAST VAULT RESTROOM BUILDING AT THE OCEAN COUNTY GOLF COURSE AT ATLANTIS, LITTLE EGG HARBOR, NJ (CONT'D)

COMPLIANCE YES NO Specifications: (Cont'd) Paint Schedule: **Interior Concrete Surfaces:** Floors – one (1) coat of 1-part water based chemical resistant urethane Walls & Ceiling – two (2) coats of a modified acrylic, water repellent penetrating stain and one (1) coat of clear acrylic X anti-graffiti sealer **Exterior Concrete Surfaces:** Walls & Roof – two (2) coats of water repellent penetrating stain in the same color as the walls or roof followed by one (1) coat of clear acrylic anti-graffiti sealer. \boxtimes Metal Surfaces (interior & exterior) П X Two (2) coats of DTM ALKYD, or approved equal Shall have a minimum thickness of Four inches (4") for the walls Vault: and Five inches (5") for the floor, all concrete design. The vaults shall have a bottom slope of one inch (1") per foot from under the toilet riser out to the outside cleanout area. The vault shall have a twenty-four inch (24") diameter (minimum) lightweight manhole cover installed to the rear of the building. The manhole cover shall be raised, with the surrounding concrete sloped away using a minimum slope of one half inch (1/2") per foot. The depth of the vault shall be no deeper than five feet (5'). \boxtimes Shall be made of Roto molded 8460 polyethylene with a minimum Vault Liner: thickness of 2.54 mm or approve equal. Liner shall have molded dovetail embeds to attached the liner to concrete walls of the vault and tow (2) welded C-channels to attach the liner to the bottom of the vault. Liner X shall hold up to 1,000 Gallons of waste per vault. Vent & Shall be a minimum of Twelve inch (12") diameter round pipe installed Stack: straight up from the vault and shall raise a minimum of 3' above the highest point of the roof. Each restroom shall have one vent and one hole. П Shall meet ADA standards, be one-piece stainless steel with seat. Riser: Ø Waterless toilet by Acorn, or approved equal. December 20, 2023 Introduced on: TAdonted on: Sh Dicembes 29 12023 of 14-gauge, type 304 stainless steel. \boxtimes

COMPLIANCE PAGES FOR FURNISHING AND INSTALLATION OF ONE (I) DOUBLE CASCADIAN STYLE PRE-CAST VAULT RESTROOM BUILDING

Page 3 of 4

ITEM #1 - FURNISHING AND INSTALLATION OF ONE (1) DOUBLE CASCADIAN STYLE PRE-CAST VAULT RESTROOM BUILDING AT THE OCEAN COUNTY GOLF COURSE AT ATLANTIS, LITTLE EGG HARBOR, NJ (CONT'D)

		COMPL	<u>IANCE</u>
		<u>YES</u>	<u>NO</u>
<u>Specification</u>	s: (Cont'd)		
Toilet Paper Dispenser:	Shall be constructed of one quarter inch (¼"), type 304 stainless steel which holds three (3) standard rolls of toilet paper. Fastening system shall be able to withstand 300-lb. top loading.	⊠	
Wall Vent:	Vend cover shall be 14-gauge, type 304 stainless steel painted with DMT ALKYD or approved equal, and anchored into the concrete wall with high strength anti-rust Tapcon fastener. Vent louver frame and louv frame and louvers shall be non-vision, 0.1" extruded aluminum jet coat finish and include an insect screen. Vent cover shall be recessed a minimum of \(^3\)4" on exterior walls with a 45° bevel, interior to be flush mounted. Wall vent shall not protrude from the wall.	er ⊠	,
**** 1 · A			
Windows &			
<u>Vault Cleano</u> Cover:	Widows and cleanout cover frames shall be constructed of steel. Window glazing is 3/16" thick translucent pebble finished mar-resistant Lexan, or approved equal. Side windows shall have ¾" recess with a 45° bevel. Window frames shall have vandal resistant fasteners. Gable window shall be constructed of a minimum 4" x 4" x ¾" square tube. Plate for the vault cleanout cover shall be ¼" thick diamond plate steel hinged and configured so it can be locked with a padlock, with gasket provided around the entire perimeter of the lid to provide		
	a tight seal.	\boxtimes	
Doors:	Shall be flush panel type 1 ¾" minimum 16-gauge galvanized steel top painted with DTM ALKYD, or approved equal. Door frames shall be knockdown or welded type, single rabbet; minimum 16-gauge prime coated steel, top painted with DTM ALKYD, or approved equal, width to suit wall thickness. There shall be three (3) hinges per door with dull chrome plating 4 ½" x 4 ½", adjustable tension, and automatic		
	closing for each door. Door sweep shall be provided at the bottom of	,	
	each door with adjustable brush.	\boxtimes	
Deadbolt: Introduced on: Adopted on:	Shall be certified ANSI/BHMA A156.5-2001 Grade 1 heavy duty tan Beernber 20, 2023 ith a 2 3/4" backset. Finish US26D;		
	io Sata 200 Marie or approved equal.	\boxtimes	. \square

Res-Pg: j.4-9
COMPLIANCE PAGES FOR FURNISHING AND INSTALLATION OF ONE (1) DOUBLE CASCADIAN STYLE PRE-CAST VAULT RESTROOM
BUILDING BUILDING Page 4 of 4

ITEM #1 - FURNISHING AND INSTALLATION OF ONE (1) DOUBLE CASCADIAN STYLE PRE-CAST VAULT RESTROOM BUILDING AT THE OCEAN COUNTY GOLF COURSE AT ATLANTIS, LITTLE EGG HARBOR, NJ (CONT'D)

COMPLIANCE

		YES	NO
Specification Lockset:	Shall meet ANSI A156.2 Series 4000, Grade 1 cylindrical lockset for exterior door with lever handle both inside and out. Either handle operates latch unless outside handle is locked by inside push-button, push button will automatically release when inside lever handle is turned or door is closed. Doors shall have an emergency slot on exterior so door can be unlocked from the outside in case of emergency. Finish US26D – Satan Chrome, or approved equal.	⊠	П
Signs:	Shall have raised pictograms, letters and braille to meet ADA standards, interior shall have "No TRASH IN VAULT" sign. All signs shall be inset a minimum of 3/4" into wall with a 45° bevel,		
9	and anchored into the concrete with 1/4" x 1/4" concrete anchor nails.	\boxtimes	
Grab Bars:	Shall be 18-gauge, type 304 stainless steel with 1½" clearance, and be able to withstand 300 lb. top loading.	⊠	
Location:	The Ocean Count Golf Course at Atlantis 261 Country Club Blvd Little Egg Harbor, NJ *Behind the 9 th tee	\boxtimes	
Warranty:	Provide a warranty against defects in material or workmanship for period of twenty (20) years. All other non-concrete components provide a one (1) year warranty.		×
Site Visit & Installation:	Prospective bidders are encouraged to visit the site to familiarize themselves with the project. Coordination of a site visit shall be made with Joseph Pirozek, Parks and Recreation, (732) 506-9090 x 5952. Upon award, vendor shall coordinate delivery with County and communicate with the County during the fabrication process. Vendor shall work with the County on all color/texture options upon award.		
Drawings:	Refer to attached drawings for reference.		

Introduced on: Adopted on:

December 20, 2023 December 20, 2023

Official Resolution#: 2023001835